

HOPE 5.0LW-B1

- Flexible capacity from 5kWh to 240kWh
- Compact size and easy installation
- High energy density and efficiency
- Excellent safety of LiFePO4 battery
- Built-in and external touch(optional) display screen
- DoD up to 92%



**Parvaneh
Trading**

بازرگانی پروانه
وارد کننده تخصصی
تجهیزات برق خورشیدی در ایران

www.parvanehco.com

01155220000

09120230322

Datasheet		HOPE 5.0LW-B1
Battery data		
Nominal voltage		51.2V
Rated capacity		5.12kWh
Usable capacity		5.0kWh
Operating voltage		40 ~ 58.4V
Max. discharging current		100A
Peak discharging current		750A,5ms
Max charging current		100A
General data		
Dimension (W/D/H)		390*152*620
Weight		<44.5kg
IP protection		IP20
Charge temperature		0°C~+55°C
Discharge temperature		-20~55°C
Installation		Wall-mounted
Features		
DOD		92%
Cycle life		>=6000 (80% DOD,25°C)
Parallel connection		Max.48 packs
Communication port		CAN/RS485
Warranty		5 Years
IEC62619/CE(EMC)/UN38.3/MSDS/ROHS		

* Nominal charge/discharge current and power derating will occur related to Temperature and SOC